



POWERING YOUR ADVENTURES

PROBOOST25

25A DC-DC CHARGER

BM PRO's ProBoost25 is a multi-stage DC-DC battery charger that enables the charging of a secondary battery using solar panels and/or a towing vehicle's 12V electrical system.



SPECIFICATIONS

Input Voltage	9-18V
Solar Input Voltage	10-25V
Maximum Input Current	27A
Input Fuse Rating	40A
Solar Input Watts	500W
Maximum Output Current	25A
Output Fuse Rating	40A
Minimum Start Voltage	Lead-Acid: 4V LiFePO4: 0V
Standby Current	<10mA
Battery Type	STD, Gel, AGM, Calcium, LiFePO4
Operating Temperature	-20°C to 80°C
IP Rating	IP56
Dimensions	145mm x 130mm x 43mm
Charge Type	3-Stage
Maximum Voltage	STD: 14.4V Gel: 14.1V AGM: 14.7V Calcium: 15.3V LiFePO4: 14.5V
Float Voltage	STD: 13.4V Gel: 13.5V AGM: 13.4V Calcium: 13.6V LiFePO4: 13.6V
Turn On Input Voltage	12V Standard Alternator: >13.1V 12V Smart Alternator: >12.0V
Turn Off Input Voltage	12V Standard Alternator: <12.8V 12V Smart Alternator: <11.8V

KEY FEATURES

- Compatible with lead-acid and lithium LiFePO4 batteries
- 25A solar MPPT regulator
- Dual input from both solar and vehicle auxiliary
- High power density design provides efficiency up to 93%
- Ultra-thin design suitable for small installation spaces, including under bonnets
- Excellent performance in harsh environments
- Resistant to shaking, wet, dusty or muddy environments
- Smart alternator compatible
- Overtemperature, overvoltage, undervoltage and reverse polarity protection



19 Henderson Rd, Knoxfield VIC 3180 Australia
Unit 1, 821 E Windsor Ave, Elkhart IN 46514 USA
customerservice@teambmp.com